

DEVICE FOR DISPLAYING ALPHANUMERIC CHARACTERS AND SYMBOLS

Patent number: WO9750070

Publication date: 1997-12-31

Inventor: RONKHOLZ KARL HEINZ (DE)

Applicant: LUMINO GMBH LICHT ELEKTRONIK (DE);
RONKHOLZ KARL HEINZ (DE)

Classification:

- international: G09F9/33

- european: G09F9/33

Application number: WO1997EP03145 19970617

Priority number(s): DE19962011155U 19960626; DE19962021296U
19961207

Also published as:



EP1004110 (A1)

EP1004110 (B1)

Cited documents:



US4689604


WO9012354

EP0156544

Report a data error here

Abstract of WO9750070

The invention concerns a device for displaying alphanumeric characters and/or symbols, with a rotationally symmetric housing (19) of a transparent and/or light transparent material; the housing (19) containing an electric motor (2) with a motor shaft (20) which revolves around a symmetrical axis (21); a carrier (5) which is rotationally fixed to the motor shaft (20) and on which is/are attached at least one row of light-emitting diodes or groups of light-emitting diodes (6) that are substantially perpendicular to the motor shaft (20); and a circuit board (4) with a control circuit for the light-emitting diodes (6). To improve control of the display device and the LED's and to create a technically simple series production, the display device also has an opto-electronic measuring device (15) made of a transmitter and receiver, to measure the rotating speed of the carrier (5) for synchronising control of the light-emitting diodes (6) with the rotating speed of the carrier (5), the transmitter and receiver of which are fixed to a rotating structural part of the device on the one hand to a stationary structural part of the device on the other hand, opposite and at a short distance apart. With the use of software the signal picked up by the receiver can be converted into a clear square-wave signal, free from external interference so that the LED-control can be synchronised with the exactly or almost exactly measured rotating speed of the carrier (5). The device according to the invention also contains a mechanical balancing element (7, 8) opposite the carrier (5) in relation to the symmetrical axis (21), wherein the balancing element (7, 8) is a rod (7) of any cross-section, the operating length of which can



BEST AVAILABLE COPY

BEST AVAILABLE COPY

be shortened, the rod being raised into a substantially horizontal position during operating.

Data supplied from the **esp@cenet** database - Worldwide

BEST AVAILABLE COPY